


NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307


ACTi											
											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
ACD2000Q	A4Q-220-V3.02.04-AC	MPEG4 M-JPEG	4	720x480	1-way	2/2	Yes	Yes	-	Yes	
ACD2100	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	720x480	1-way	2/2	Yes	Yes	-	Yes	
ACD2200		MPEG4 M-JPEG	4	720x480	1-way	8/8	Yes	Yes	-	Yes	Supported by design
ACD2300		MPEG4 M-JPEG	8	720x480	1-way	16/16	Yes	Yes	-	Yes	Supported by design
ACD2400	AGD-R2N-V2.05.02-AC	MPEG4 M-JPEG	16	720x480	1-way	32/32	Yes	Yes	-	Yes	
ACM1011	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	
ACM1231		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM1232		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM1311		MPEG4 M-JPEG	1	720x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM1431		MPEG4 M-JPEG	1	720x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM1432		MPEG4 M-JPEG	1	720x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM1511		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM3001		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM3011		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM3211		MPEG4 M-JPEG	1	720x480	1-way	-	Yes	Yes	-	Yes	Supported by design
ACM3311		MPEG4 M-JPEG	1	720x480	1-way	-	Yes	Yes	-	Yes	Supported by design
ACM3401		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM3411		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM3511		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307


ACTi											
											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
ACM3601	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	
ACM3603		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Supported by design
ACM3701	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	
ACM3703		MPEG4 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	Supported by design
ACM4000		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM4001		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design
ACM4100	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	
ACM4200		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM4201		MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design
ACM5001		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Yes	Supported by design
ACM5601	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Yes	
ACM5611		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Yes	Supported by design
ACM5711	A1D-220-V3.08.08-AC	MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	Yes	
ACM5811	A1D-220-V3.12.13-AC	MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	Yes	
ACM7411	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Yes	
Note:	A1D-220-V3.09.14-AC: There is problem at 160x112 resolution.										
ACM7511	A1D-220-V3.12.13-AC	MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	Yes	
ACM8201	A1D-220-V3.10.22-AC	MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes	
Note:	A1D-220-V3.09.14-AC: There is problem at 160x112 resolution.										
ACM8211	A1D-220-V3.09.14-AC	MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec




NUUO version 2.5.3_release date_110307

ACTi											
											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
ACM8511	A1D-220-V3.11.13-AC	MPEG4 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	Yes	
AMU9401	A1D-220-V3.10.22-NB	MPEG4 M-JPEG	1	1280x1024	1-way	0/0	-	Yes	-	Yes	
AMU9711	A1D-220-V3.10.22-NB	MPEG4 M-JPEG	1	1280x1024	1-way	0/0	-	Yes	-	Yes	Supported by design
CAM5130		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM5140		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM5150		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM5200		MPEG4	1	720x480	-	1/1	-	Yes	-	Yes	Supported by design
CAM5201		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM5221	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	
CAM5300		MPEG4	1	720x480	-	1/1	-	Yes	-	Yes	Supported by design
CAM5301		MPEG4	1	720x480	-	1/1	-	Yes	-	Yes	Supported by design
CAM5321		MPEG4	1	720x480	-	1/1	-	Yes	-	Yes	Supported by design
CAM5500		MPEG4	1	720x480	-	1/1	-	Yes	-	Yes	Supported by design
CAM6100		MPEG4	1	720x480	-	2/2	Yes	Yes	-	Yes	Supported by design
CAM6200	A1D-2.07.14-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	Yes	Supported by design
CAM6220	A1D-2.07.14-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	Yes	Supported by design
CAM6500		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
CAM6510	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	
CAM6520		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

ACTi											
											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
CAM6600		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
CAM6610		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
CAM6620		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
CAM6630		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
CAM7100		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7120		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7200		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7220		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7300		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7301		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7320		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7321		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
CAM7322		MPEG4	1	720x480	1-way	1/1	-	Yes	-	Yes	Supported by design
SED2100		MPEG4	1	720x480	1-way	2/2	-	Yes	-	Yes	Supported by design
SED2120	A1D-M2N-V2.08.11-AC	MPEG4	1	720x480	-	2/2	Yes	Yes	-	Yes	
SED2140		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
SED2310Q		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
SED2320Q		MPEG4	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
SED2400		MPEG4	2	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307


ACTi											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
SED2420	A1D-220-V3.08.08-AC	MPEG4	2	720x480	1-way	-	-	Yes	-	Yes	
SED2600		MPEG4	8	720x480	1-way	16/16	Yes	Yes	-	Yes	Supported by design
SED2610		MPEG4	8	720x480	1-way	16/16	Yes	Yes	-	Yes	Supported by design
SED26X0		MPEG4	8	720x480	1-way	16/16	Yes	Yes	-	Yes	Supported by design
TCD2100	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	720x480	-	1/1	Yes	Yes	Yes	Yes	
TCD2500	A1D-310-V4.06.08-AC	H.264 MPEG4 M-JPEG	1	720x480	1-way	2/1	Yes	Yes	Yes	Yes	
TCM1231	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
TCM1232		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
TCM1511	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
TCM3001		H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
TCM3011	A1D-310-V4.07.10-AC	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
TCM3401		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
TCM3411	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
TCM3511	A1D-310-V4.06.00-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
TCM4101		H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes	Supported by design
TCM4201	A1D-310-V4.07.15-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
TCM4301	A1D-310-V4.05.13-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307

ACTi											
											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
TCM5001	A1D-310-V4.07.15-AC	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
TCM5311	A1D-310-V4.05.13-AC	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	-	Yes	
TCM5312		H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	Yes	Supported by design
TCM5601	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	Yes	Yes	Supported by design
TCM5611	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	Yes	Yes	
TCM7011	A1D-310-V4.06.09-AC	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
TCM7411		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	Yes	Yes	Supported by design
TMU9811	A1D-310-V4.07.10-NB	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	-	Yes	
TMU9911	A1D-310-V4.07.10-NB	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	-	-	Yes	Supported by design
Note:	ACD / ACM series cameras do not support FW 3.11.11.										
Note:	Only two I/O are shown on the interface as adding one channel on video server.										

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307

Arecont



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
AV1300	64328	M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	Supported by design
AV1305	64331	H.264 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	
AV1310		M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	Supported by design
AV1355	65130	H.264 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	Supported by design
AV2000	64328	M-JPEG	1	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV2100	64328	M-JPEG	1	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV2105	64331	H.264 M-JPEG	1	1600x1184	-	-	-	Yes	-	Yes	
AV2110		M-JPEG	1	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV2155	64803	H.264 M-JPEG	1	1600x1184	-	-	-	Yes	-	Yes	
AV2805	65150	H.264 M-JPEG	1	1920x1080	-	1/1	-	Yes	-	Yes	
AV3100	64328	M-JPEG	1	2048x1536	-	-	-	Yes	-	Yes	Supported by design
AV3105	64331	H.264 M-JPEG	1	2048x1536	-	-	-	Yes	-	Yes	
AV3110		M-JPEG	1	1920x1216	-	-	-	Yes	-	Yes	Supported by design
AV3130	61906	M-JPEG	1	2048x1536	-	-	-	Need to retest	-	Yes	Supported by design
AV3135	65135	H.264 M-JPEG	1	2048x1536	-	1/1	-	Yes	-	Yes	
AV3155	65113	H.264 M-JPEG	1	2048x1536	-	-	-	Yes	-	Yes	
AV5100	61906	M-JPEG	1	2560x1600	-	-	-	Yes	-	Yes	
AV5105	64331	H.264 M-JPEG	1	2560x1600	-	1/1	-	Yes	-	Yes	
AV5110		M-JPEG	1	2560x1600	-	-	-	Yes	-	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307

Arecont



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
AV5155	65113	H.264 M-JPEG	1	2560x1600	-	-	-	Yes	-	Yes	
AV8180	65010	M-JPEG	4	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV8185	64803	H.264 M-JPEG	4	1600x1200	-	-	-	Yes	-	Yes	
AV8360	65010	M-JPEG	4	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV8365	65026	H.264 M-JPEG	4	1600x1184	-	-	-	Yes	-	Yes	Supported by design
AV10005	65147	H.264 M-JPEG	1	3648x2752	-	-	-	Yes	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

ARM



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
MP13DDNWD		MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	-	Supported by design
MP13VPDN		MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
205		M-JPEG	1	640x480	-	-	-	Yes	-	Supported by design
206		M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
206M		M-JPEG	1	1280x1024	-	-	-	Yes	Yes	Supported by design
206W		M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
207	4.40	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
207MW		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
207W		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
Note:	Not support audio in M-JPEG									
209FD		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
209FD-R		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
209MFD		MPEG4 M-JPEG	1	1280x1024	-	-	Yes	Yes	Yes	Supported by design
209MFD-R		MPEG4 M-JPEG	1	1280x1024	-	-	Yes	Yes	Yes	Supported by design
210		MPEG4 M-JPEG	1	640x480	-	1/1		Yes	Yes	Supported by design
210A	4.40	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
211		MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	Yes	Supported by design
211A		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
211M		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
211W		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
212 PTZ		MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
213 PTZ		MPEG4 M-JPEG	1	704x576	1-way	2/3	Yes	Yes	Yes	Supported by design
214 PTZ	4.33	MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	Yes	Yes	
215 PTZ		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
216FD		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
216FD-V		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
216MFD		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
216MFD-V		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
221		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Supported by design
223M		MPEG4 M-JPEG	1	1600x1200	1-way	2/1	-	Yes	Yes	Supported by design
225FD		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Supported by design
231D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	Yes	Yes	Supported by design
232D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes	Yes	Yes	Supported by design
233D		MPEG4 M-JPEG	1	704x576	1-way	4/4	Yes	Yes	Yes	Supported by design
2400		M-JEPG	4	704x576	-	4/1	-	Yes	Yes	Supported by design
240Q		M-JEPG	4	704x576	-	4/4	-	Yes	Yes	Supported by design
241Q		MPEG4 M-JPEG	4	704x576	-	4/4	-	Yes	Yes	Supported by design
241QA	4.30	MPEG4 M-JPEG	4	704x576	1-way	4/4	-	Yes	Yes	
241S		MPEG4 M-JPEG	1	704x576	-	4/4	-	Yes	Yes	Supported by design
241SA		MPEG4 M-JPEG	1	704x576	1-way	4/4	-	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
242S		MPEG4 M-JPEG	1	704x576	-	4/4	-	Yes	Yes	Supported by design
243Q		MPEG4 M-JPEG	1	704x576	-	1/1	-	Yes	Yes	Supported by design
243SA		MPEG4 M-JPEG	1	704x576	1-way	4/4	-	Yes	Yes	Supported by design
2460		M-JEPG	4	704x576	-	4/1	-	Yes	Yes	Supported by design
247S		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
M1011	5.00	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	
M1011-W	5.00	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	
M1031-W	5.00	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	
M1054	5.15	H.264 M-JPEG	1	1024x640	1-way	1/1	-	Yes	Yes	
M1113	5.08	H.264 M-JPEG	1	800x600	-	-	Yes	Yes	Yes	*
M3011	5.01	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
M3014		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Supported by design
M3114-R	5.11	H.264 M-JPEG	1	1280x800	-	-	Yes	Yes	Yes	
M3203		H.264 M-JPEG	1	800x600	-	-	-	Yes	Yes	Supported by design
M3203-V		H.264 M-JPEG	1	800x600	-	-	-	Yes	Yes	Supported by design
M3204		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Supported by design
M3204-V		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Supported by design
P1311	5.01	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
P1343	5.06	H.264 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	*

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
P1344		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	Supported by design
P1346	5.06	H.264 M-JPEG	1	2048x1536	1-way	1/1	Yes	Yes	Yes	*
P3301	5.11	H.264 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
P3301-V		H.264 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
P3343	5.06	H.264 M-JPEG	1	800x600	1-way	1/1	Yes	Yes	Yes	Supported by design
P3343-V		H.264 M-JPEG	1	800x600	1-way	1/1	Yes	Yes	Yes	Supported by design
P3343-VE		H.264 M-JPEG	1	800x600	1-way	1/1	Yes	Yes	Yes	Supported by design
P3344	5.06	H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	
P3344-V	5.06	H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	
P3344-VE	5.06	H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	
Note:	P3343 and P3344 series cameras support digital PTZ only.									
P5534	5.15.1	H.264 M-JPEG	1	1280x720	1-way	2/2	Yes	Yes	Yes	Supported by design
P8221	5.10	H.264 MPEG4	1	-	1-way	4/4	-	-	Yes	
Q1755	5.02	H.264 M-JPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	
Note:	M-JPEG: Due to the HW constraints, the frame rate and audio will be impacted if resolution and quality are high.									
Q1910	5.06	H.264 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	
Q1910-E		H.264 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
Q6032-E	5.05	H.264 M-JPEG	1	704x576	-	-	Yes	Yes	Yes	
Q7401		H.264 M-JPEG	1	704x576	1-way	2/2	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

AXIS										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Q7404	5.02	H.264 M-JPEG	4	768x576	1-way	1/1	Yes	Yes	Yes	
Q7406		H.264 M-JPEG	6	704x576	-	1/1	Yes	Yes	Yes	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Basler										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BIP-640c		H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	-	-	Tested by manufacturer
BIP-640c-dn		H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	-	-	Tested by manufacturer
BIP-1000c		H.264 MPEG4 M-JPEG	1	1024x768	-	1/1	-	-	-	Tested by manufacturer
BIP-1000c-dn		H.264 MPEG4 M-JPEG	1	1024x768	-	1/1	-	-	-	Tested by manufacturer
BIP-1300c		H.264 MPEG4 M-JPEG	1	1280x960	-	1/1	-	-	-	Tested by manufacturer
BIP-1300c-dn	BIP-1300c-dn-1.6-2	H.264 MPEG4 M-JPEG	1	1280x960	-	1/1	-	Yes	-	
Note:	On-Edge Motion: H.264 and M-JPEG.									
BIP-1600c		H.264 MPEG4 M-JPEG	1	1600x1200	-	1/1	-	-	-	Tested by manufacturer
BIP-1600c-dn		H.264 MPEG4 M-JPEG	1	1600x1200	-	1/1	-	-	-	Tested by manufacturer
BIP-D1000c-dn		H.264 MPEG4 M-JPEG	1	1024x768	-	1/1	-	-	-	Tested by manufacturer
BIP-D1300c-dn	BIP-D1300c-dn-1.6-1	H.264 MPEG4 M-JPEG	1	1280x960	-	1/1	-	Yes	-	
Note:	On-Edge Motion: H.264 and M-JPEG.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

BOSCH										
 BOSCH Invented for life										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
NWC-0455	19500410	H.264 M-JPEG	1	704x576	-	-	-	-	-	


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Brickcom										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
CB-100Ae	v3.0.2.4	MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	Tested by manufacturer
CB-100Ap	v3.0.2.4	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	Tested by manufacturer
FB-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	Tested by manufacturer
FB-100Ap	v3.0.2.3	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	Tested by manufacturer
FD-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	Tested by manufacturer
FD-100Ap	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	
WCB-100Ae	v3.0.2.4	MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	Tested by manufacturer
WCB-100Ap	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	
WFB-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	Tested by manufacturer
WFB-100Ap	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/0	-	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

CISCO										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
CIVS-IPC-2500	V1.1.3R15	MPEG4 M-JPEG	1	720x480	1-way	2/2	-	-	Yes	
CIVS-IPC-2500W	V1.1.3R03	MPEG4 M-JPEG	1	720x480	1-way	2/2	-	-	Yes	
PVC-300	1.0.0	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ is only supported by external RS-485 device.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

CNB										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IBE3815NVR		H.264 MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	Yes	Supported by design
IBE3815PVR		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
IBE5810NCR		H.264 MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	Yes	Supported by design
IBE5810PCR		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
IDP4000VD	XNET.A1-1.1.9.1104	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	
IDP4000VR	XNET.A1-1.1.9.1104	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	
IDP4030VR		H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	-	-	Yes	Supported by design
IGP1000		H.264 MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	Yes	Supported by design
IGP1030	XNET.A1-1.1.9.1104	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	-	Yes	
IJB2000		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
INS2000	XNET.A1-1.1.9.1104	H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	
IPM3063N		H.264 MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	Yes	Supported by design
IPM3063P		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
ISMC1063N		H.264 MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	Yes	Supported by design
ISMC1063P		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
ISS2765NW		H.264 MPEG4 M-JPEG	1	704x480	1-way	-	Yes	-	Yes	Supported by design
ISS2765PW		H.264 MPEG4 M-JPEG	1	704x576	1-way	-	Yes	-	Yes	Supported by design
IVP4000VR	XNET.A1-1.1.9.1028	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	
IVP4030VR		H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	-	-	Yes	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

D-Link										
 Building Networks For People										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DCS-1100	1.00	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
DCS-1130	1.00	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
DCS-2100		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design
DCS-2100G		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design
DCS-2102		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
DCS-2120(TW)	0201tw	MPEG4	1	720x576	1-way	1/1	-	Yes	Yes	
DCS-2120		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
DCS-2121		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
DCS-3110		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
DCS-3220		MPEG4	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
DCS-3220G		MPEG4	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
DCS-3410		MPEG4 M-JPEG	1	704x576	1-way	2/1	-	Yes	Yes	Supported by design
DCS-3415	1.00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
Note:	PTZ Support: zoom only.									
DCS-3420		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
DCS-5220(TW)		MPEG4	1	720x576	1-way	-	Yes	Yes	Yes	Supported by design
DCS-5220	0200	MPEG4	1	720x576	1-way	-	Yes	Yes	Yes	
DCS-5300	1.05	MPEG4	1	704x576	1-way	1/1	Yes	Yes	Yes	
DCS-5300G		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

D-Link										
 Building Networks For People										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DCS-5610		MPEG4 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DCS-6110	1.00	M-JPEG	1	720x576	-	1/1	-	Yes	Yes	
DCS-6111	1.00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
DCS-6410	1.00	MPEG4 M-JPEG	1	704x576	1-way	2/1	-	Yes	Yes	Supported by design
DCS-6620	1.05	MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	
DCS-6620G	1.05	MPEG4 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	
DCS-7510	1.00	MPEG4 M-JPEG	1	704x576	1-way	2/1	-	Yes	Yes	Supported by design
DCS-900	1.00	MPEG4	1	640x480	1-way	-	-	-	Yes	Supported by design
DCS-910	1.00	MPEG4	1	640x480	-	-	-	-	Yes	Supported by design
DCS-920		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
DCS-950		MPEG4	1	640x480	1-way	-	-	-	Yes	Supported by design
DCS-950G		MPEG4	1	640x480	1-way	-	-	-	Yes	Supported by design
DCS-G900		M-JPEG	1	640x480	-	-	-	-	Yes	Supported by design
DVS-104		M-JPEG	4	720x576	-	4/2	-	Yes	Yes	Supported by design
DVS-301		H.263	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

DYNACOLOR										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
NH061-CCD	CCD-cameraFw-100205P	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	
Note:	Camera FW is not stable enough, so camera is likely disconnected after modifying parameters. Current workaround is turning off and on to reboot camera. Remove resolution 1280x720 in H.264 codec due to broken image problem. Known FW issue: audio may be broken in certain operation.									
NH221-CCD	CCD-cameraFw-100205P	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	
Note:	Remove resolution 1280x720 in H.264 codec due to broken image problem. The image is broken badly when configuring to the highest resolution, fps, and quality under H.264/MPEG4 with UDP protocol. Known FW issue: audio may be broken in certain operation.									
V1-A		H.264 M-JPEG	1	1920x1080	-	-	-	Yes	Yes	Supported by design
V1-B	d20100630NS	H.264 M-JPEG	1	1920x1080	1-way	-	-	Yes	Yes	
Note:	There is high possibility to get broken image on the edge under H.264 codec with UDP protocol.									
V2-A		H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	Supported by design
V2-B	d20100826NS	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
V6-A		H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	Supported by design
V6-B	d20100630NS	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
Note:	The image is broken badly when configuring to the highest resolution, fps, quality, etc.									
Note:	Model A is referred to model B, promised by the manufacturer, so model A may encounter same issues of model B.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Eneo										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
GLC-1401	1.42	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	Yes	Yes	Supported by design
GLC-1601	1.43	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	Yes	Yes	
GLC-1602H	1.43	H.264 M-JPEG	1	720x576	1-way	1/0	Yes	Yes	Yes	
GLC-1610H		H.264 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	Yes	Supported by design
GLC-1701/IR	1.45	MPEG4 M-JPEG	1	720x576	-	1/0	-	Yes	Yes	
GLD-1401	1.40	MPEG4 M-JPEG	1	720x576	-	1/0	-	Yes	Yes	
GLD-1501	1.43	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	Yes	Yes	
GLS-2101	1.45	MPEG4 M-JPEG	1	720x576	1-way	1/0	Yes	Yes	Yes	
GLS-2104	1.78	M-JPEG	4	704x272	1-way	-	Yes	Yes	Yes	
GLS-2301H	1.09	H.264 M-JPEG	1	720x480	1-way	-	-	Yes	Yes	
NLC-1401	v1.5.6	H.264 MPEG4	1	704x576	1-way	1/0	Yes	Yes	Yes	
NLD-1401	v1.5.6	H.264 MPEG4	1	704x576	1-way	1/0	-	Yes	Yes	
NLS-1401	v1.5.6	H.264 MPEG4	1	704x576	1-way	2/0	Yes	Yes	Yes	
NXC-1301M	v2.1.2	H.264	1	1280x720	-	2/0	-	Yes	Yes	
NXC-1302M	v2.1.2	H.264	1	1600x1200	-	2/0	-	Yes	Yes	
NXC-1401M	v2.1.2	H.264	1	1280x720	-	2/0	-	Yes	Yes	
NXC-1402M	v2.1.2	H.264	1	1600x1200	-	2/0	-	Yes	Yes	
NXD-1301M	v2.1.2	H.264	1	1280x720	-	2/0	-	Yes	Yes	
NXD-1302M	v2.1.2	H.264	1	1600x1200	-	2/0	-	Yes	Yes	


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Eneo										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
NXD-1401M	v2.1.2	H.264	1	1280x720	-	2/0	-	Yes	Yes	
NXD-1402M	v2.1.2	H.264	1	1600x1200	-	2/0	-	Yes	Yes	
Note:	Audio is disabled currently for camera FW bug: NXC-1301M, NXC-1302M, NXC-1401M, NXC-1402M, NXD-1301M, NXD-1302M, NXD-1401M and NXD-1402M									
Note:	PTZ is only supported by external RS-485 device.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Fine										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
CDV-3V930		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CDV-3V930U		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	Supported by design
CDV-3VM301		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Supported by design
CDV-3VM501		H.264 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	-	Supported by design
CDV-3VWD960	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	
CDV-3VWD960H		H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	Supported by design
EP-201		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-221		MPEG4 M-JPEG	1	720x480	1-way	1/0	Yes	Yes	-	Supported by design
EP-221DN		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-601		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-601HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-908		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-908HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-936		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-936HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-HTQ935	V3.2.56_F	MPEG4 M-JPEG	1	720x480	-	0/0	Yes	Yes	-	
EP-Q2018H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-Q2018HW-IP	V1.0.8_F	H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	
EP-Q2026H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Fine										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
EP-Q2026HW-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-Q2036H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
EP-Q2036HW-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	Supported by design
MD-D1200		MPEG4 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	Supported by design
MD-D1612	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	-	
SP-PTIR737-IP	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	0/0	Yes	Yes	-	
TCMA-99		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Supported by design
TCMP-99		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Supported by design
TCP-670DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-680DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-690DN		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-690U	V3.2.60_F	MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	
TCP-HP930		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-HP930U		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-IPWD690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	Supported by design
TCP-IPWD700DN	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	
TCP-IRV540		MPEG4 M-JPEG	1	720x480	1-way	0/0	-	Yes	-	Supported by design
TCP-IRV560		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Fine										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
TCP-M912DN	V1.2.28_F	MPEG4 M-JPEG	1	MPEG4: 640x480 M-JPEG: 1280x960	1-way	2/2	-	Yes	-	
TCP-MH802	V1.0.8_F	H.264 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	-	
TCP-VM201		MPEG4 M-JPEG	1	1280x1024	1-way	0/0	-	Yes	-	Supported by design
TCP-VM501	V1.0.14_F	H.264 M-JPEG	1	1600x1200	1-way	1/1	-	yes	-	
WB-8211SD		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	Supported by design
WB-8211SDU		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	Supported by design
WB-8411		MPEG4 M-JPEG	4	720x480	1-way	4/1	-	Yes	-	Supported by design
WB-8412	V2.2.26_F	MPEG4 M-JPEG	4	688x448	1-way	4/4	Yes	Yes	-	
WB-H811		H.264 M-JPEG	1	720x480	1-way	2/2	Yes	Yes	-	Supported by design
WB-H814	V1.0.40_F	H.264 M-JPEG	4	720x576	1-way	4/4	Yes	Yes	-	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

HIKVISION										
										
New-platform models: FW 20100628 is compatible Old-platform models: only FW 20100320 is acceptable										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD702NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD702PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD712NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD712PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD7133-E	V2.0 100628	H.264	1	640x480	-	-	-	Yes	-	
DS-2CD7153-E	V2.0 100628	H.264	1	1600x1200	-	-	-	Yes	-	
DS-2CD732F-E	20100320	H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	
DS-2CD733F-E	V2.0 100716	H.264	1	640x480	1-way	2/2	Yes	Yes	-	Tested by manufacturer
DS-2CD752MF-E		H.264	1	1600x1200	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD752MF-FB	20100320	H.264	1	1600x1200	1-way	1/1	Yes	Yes	Yes	
DS-2CD753F-E	V2.0 100628	H.264	1	1600x1200	1-way	2/2	Yes	Yes	-	Tested by manufacturer
DS-2CD762MF-FB	20100320	H.264	1	1280x960	1-way	1/1	Yes	Yes	Yes	
DS-2CD792NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD792PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD793PFW D-E	V2.0 100628	H.264	1	704x576	1-way	2/2	Yes	Yes	No	Tested by manufacturer
DS-2CD802NF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802NF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802PF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

HIKVISION										
										
New-platform models: FW 20100628 is compatible Old-platform models: only FW 20100320 is acceptable										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD802PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802PF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802N-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802N-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802N-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802P-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802P-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD802P-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812NF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812NF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812PF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812PF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812N-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812N-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812N-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812P-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD812P-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

HIKVISION										
										
New-platform models: FW 20100628 is compatible Old-platform models: only FW 20100320 is acceptable										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DS-2CD812P-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD832F		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD832F-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD852MF-E	20100320	H.264	1	1600x1200	1-way	1/1	Yes	Yes	Yes	
DS-2CD862MF-E		H.264	1	1280x960	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD863PF-E	V2.0 100628	H.264	1	1280x960	1-way	1/1	Yes	Yes	-	Tested by manufacturer
DS-2CD892NF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892NF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892NF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892PF		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892PF-E		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892PF-W		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892N-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892N-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892N-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892P-IR1		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892P-IR3		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
DS-2CD892P-IR5		H.264	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ is only supported by external RS-485 device.									


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Honeywell										
Honeywell										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ACUIX	1.5.6	MPEG4	1	4CIF	-	-	Yes	-	-	
Note:	Sometimes the PTZ function doesn't work properly due to camera FW; users have to restart to make it work. The speed of PTZ is not correspondent with camera web, which might be due to camera FW.									
HCD554IP	5.4.5	MPEG4	1	4CIF	1-way	0/1	-	-	-	
Note:	Disable input function due to camera FW.									
HD3MDIP	7.07	MPEG4	1	1280x720	1-way	-	-	Yes	-	
HD4MDIP	8.04	MPEG4	1	1280x720	1-way	-	-	Yes	-	
HNVE1	6.3.4	MPEG4	1	4CIF	1-way	-	-	-	-	
Note:	Disable I/O function due to camera FW.									
Note:	HD3MDIP, HD4MDIP: Not support I/O currently. All models: Users may be confused because the username on login page of camera web is "administrator", but it's "admin" actually. If you type in "administrator", you are no longer to connect the cameras.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

IQinVision										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IQ040S		M-JPEG	1	720x480	-	-	-	Yes	-	Supported by design
IQ041S		M-JPEG	1	1280x1024	-	-	-	Yes	-	Supported by design
IQ042S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	Yes	-	
IQ540S		M-JPEG	1	720x480	-	-	-	Yes	-	Supported by design
IQ541S		M-JPEG	1	1280x1024	-	-	-	Yes	-	Supported by design
IQ542S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	Yes	-	
IQA15N	V3.0/8(100702)	M-JPEG	1	2560x1920	-	1/1	-	Yes	-	
IQA25S	V2.9/6	M-JPEG	1	1280x1024	-	1/1	-	-	-	
IQD30S	V3.1/6	H.264 M-JPEG	1	720x480	1-way	-	-	Yes	-	
Note:	Not support audio in M-JPEG.									
IQD31S	V3.1/6	H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	
Note:	Not support audio in M-JPEG									
IQD40S		M-JPEG	1	720x480	-	-	-	Yes	-	Supported by design
IQD41S		M-JPEG	1	1280x1024	-	-	-	Yes	-	Supported by design
IQD42S	V3.1/6	M-JPEG	1	1600x1200	-	-	-	Yes	-	
IQeye301		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye301m		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye301w		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye302		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye302w		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

IQinVision										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IQeye303		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye303w		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye501		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	
IQeye510	B2.8/608	M-JPEG	1	752x480	-	-	-	Yes	-	
IQeye511	V2.8/6	M-JPEG	1	1280x1024	-	-	-	Yes	-	
IQeye601		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye602		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye603		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye701	V2.8/6	M-JPEG	1	1280x1024	-	1/1	-	Yes	-	
IQeye702	V2.8/6	M-JPEG	1	1600x1200	-	1/1	-	Yes	-	
IQeye703	V2.8/6	M-JPEG	1	2048x1536	-	1/1	-	Yes	-	
IQeye705	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	Yes	-	
IQeye751		M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Supported by design
IQeye752	V2.8/6	M-JPEG	1	1600x1200	-	1/1	-	Yes	-	
IQeye753		M-JPEG	1	2048x1536	-	1/1	-	Yes	-	Supported by design
IQeye755	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	Yes	-	
IQeye855	V2.8/6	M-JPEG	1	2560x1920	-	1/1	-	Yes	-	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

LevelOne										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FCS-0010		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	Supported by design
FCS-0020		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	Supported by design
FCS-1010	0102d	H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	
FCS-1030V1.0		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design
FCS-1030V2.0		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
FCS-1040	0102a	MPEG4 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	
FCS-1050		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
FCS-1060	0202a	MPEG4	1	720x576	1-way	-	Yes	Yes	Yes	
FCS-1070		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
FCS-1081		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
FCS-1081A		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
FCS-1091		MPEG4 M-JPEG	1	640x480	1-way	2/2	-	-	Yes	Supported by design
FCS-1101		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
FCS-3000	0101a	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	
FCS-3021		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
FCS-4010		MPEG4 M-JPEG	1	720x576	1-way	4/1	Yes	Yes	Yes	Supported by design
FCS-4x00		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
FCS-5011	0100c	MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	
FCS-5030	0100a2	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

LevelOne										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
Note: No audio support in M-JPEG.										
FCS-7011		MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
WCS-0010		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	Yes	Supported by design
WCS-0020		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	Yes	Supported by design
WCS-1090		MPEG4 M-JPEG	1	640x480	1-way	2/2	-	-	Yes	Supported by design
WCS-2010V1.0		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
WCS-2010V2.0		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
WCS-2030V1.0	0200d	H.263	1	720x576	1-way	-	-	Yes	Yes	
WCS-2030V2.0		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design
WCS-2030V3.0		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
WCS-2040	0101b	MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	
WCS-2060		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
WCS-2070	0100b	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Linksys										
 A Division of Cisco Systems, Inc.										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
PVC2300	V1.1.0(xVC2300_FW_V1.1.0R05)	MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	-	Yes	
WVC210		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	Yes	
WVC2300	V1.1.0(xVC2300_FW_V1.1.0R05)	MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	-	Yes	
Note:	PTZ is only supported by external RS-485 device.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

Lumenera										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
le045c		M-JPEG	1	720x480	-	-	-	-	-	Supported by design
le045c-dn		M-JPEG	1	720x480	-	-	-	-	-	Supported by design
le075c		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
le075c-dn		M-JPEG	1	640x480	-	-	-	-	-	Supported by design
le11059c		M-JPEG	1	4000x2656	-	-	-	-	-	Supported by design
le165c		M-JPEG	1	1376x1032	-	-	-	-	-	Supported by design
le165c-dn		M-JPEG	1	1376x1032	-	-	-	-	-	Supported by design
le175c		M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
le175c-dn		M-JPEG	1	1280x1024	-	-	-	-	-	Supported by design
le259c		M-JPEG	1	1920x1080	-	-	-	-	-	Supported by design
le275c		M-JPEG	1	1600x1200	-	-	-	-	-	Supported by design
le275c-dn		M-JPEG	1	1600x1200	-	-	-	-	-	Supported by design
le375c		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
le375c-dn		M-JPEG	1	2048x1536	-	-	-	-	-	Supported by design
li165c	5626	M-JPEG	1	1376x1032	-	-	-	-	-	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
D12D-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
D12D-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Supported by design
D22M-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
D22M-IT	MX-V3.4.0.9	MxPEG M-JPEG	1	640x480	1-way	2/2	-	Yes	-	Supported by design
D22M-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Supported by design
D24-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
D24-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
D24-Sec	MX-V4.0.1.15 (2009-07-20)	MxPEG M-JPEG	1	2048x1536	1-way	2/2	-	Yes	-	
M10D	M10-V2.2.2.17	MJPEG	1	2048x1536	1-way	-	-	Yes	-	
M12D-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
M12D-Sec	MX-V3.4.0.9	MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	
M12D-Web		MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Supported by design
M22M-IT		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
M22M-Sec		MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Supported by design
Q22M-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
Q22M-Sec	MX-V3.4.5.10	MxPEG M-JPEG	1	2048x1536	1-way	2/2	-	Yes	-	Supported by design
Q24-Basic		MxPEG M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
Q24-Sec	MX-V4.0.1.7	MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NetworkCamera



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
GE-100-CB	v1.0.0.15	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	
GP-100-CB	v1.0.0.13	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	
WGE-100-CB	v1.0.0.13	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	
WGP-100-CB	v1.0.0.16	H.264 MPEG4 M-JPEG	1	1280x800	1-way	-	-	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

ONVIF




Brand	Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BOSCH	NWC-0455	19500410	H.264 M-JPEG	1	704x576	-	-	-	-	-	

Note: ONVIF specification must be fully implemented by camera vendors in order to be supported by NUUO software. To confirm the compatibility, it is recommended to execute testing prior to any further usage. The above product has been verified by NUUO.

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BB-HCE481		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Supported by design
BB-HCM100	1.3	M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	
BB-HCM110	1.3	M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	
BB-HCM311		M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Supported by design
BB-HCM331	1.3	M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	
BB-HCM371		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Supported by design
BB-HCM381	1.3	M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	
BB-HCM403		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Supported by design
BB-HCM511	1.3	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	
BB-HCM515	3.11R01	MPEG4 M-JPEG	1	1280x1024	1-way	2/1	-	Yes	Yes	
Note:	No audio support in M-JPEG @ 1280x1024.									
BB-HCM527		MPEG4 M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Supported by design
BB-HCM531	3.51R00	MPEG4 M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	
BB-HCM547A	3.60R00	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	
Note:	The camera is tested by link, so some functions can't be verified.									
BB-HCM580		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Supported by design
BB-HCM581	1.3	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	
BB-HCM701	4.30R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	
BB-HCM705	4.11R01	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/0	-	Yes	Yes	
BB-HCM715		H.264 MPEG4 M-JPEG	1	1280x960	1-way	2/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
BB-HCM735	1.05-03 (100303-02)	H.264 MPEG4 M-JPEG	1	1280x960	1-way	2/1	Yes	Yes	Yes	
BB-HCS301		M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
BL-C1		M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
BL-C10		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	Supported by design
BL-C101	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	
BL-C111	3.10R01	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	
BL-C121	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
BL-C131		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
BL-C140A	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	
BL-C160	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	
BL-C20		M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
BL-C210	4.31R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	
BL-C30		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	Supported by design
KX-HCM110		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Supported by design
KX-HCM280A		M-JPEG	1	640x480	-	1/1	-	Yes	Yes	Supported by design
DG-NF282		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
DG-NF302	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Supported by design
DG-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
DG-NP244		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
DG-NP304	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Supported by design
DG-NS202		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
DG-NS202A	2.6	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	
DG-NS950	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
DG-NS954	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
DG-NW960	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
DG-NW964	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
WJ-GXE500	1.03	H.264 MPEG4 M-JPEG	4	720x480	1-way	-	-	Yes	-	
Note:	Motion detection works abnormally when "face detection" function is enabled. Not support PTZ currently.									
WJ-NT304	1.04	M-JPEG	4	640x480	-	-	Yes	-	-	
WJ-NT314		M-JPEG	4	640x480	1-way	-	Yes	-	-	Supported by design
WV-NF284		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
WV-NF302	1.40E4_1.06	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	
WV-NM100		MPEG4 M-JPEG	1	640x480	-	-	Yes	-	-	Supported by design
WV-NP1000		M-JPEG	1	1280x960	1-way	-	-	Yes	-	Supported by design
WV-NP1004	1.21	M-JPEG	1	1280x960	1-way	-	-	Yes	-	
WV-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
WV-NP244		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Supported by design
WV-NP304	1.50E5_1.06	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

Panasonic										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
WV-NP472		M-JPEG	1	640x480	-	-	-	Yes	-	Supported by design
WV-NP502	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	-	-	Yes	-	
WV-NS202		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
WV-NS202A	2.6	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
WV-NS324		M-JPEG	1	640x480	-	-	Yes	Yes	-	Supported by design
WV-NS950	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
WV-NS954	1.06E0	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	
Note:	Audio is abnormal in MPEG4 format.									
WV-SF336	1.05	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	
Note:	Motion detection works abnormally when "face detection" function is enabled.									
WV-SP306	1.04	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	
Note:	Motion detection works abnormally when "face detection" function is enabled.									
WV-NW484S	1.10ED	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	-	
WV-NW502S	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	-	-	Yes	-	
WV-NW960	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design
WV-NW964		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

PiXORD										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
P600	2.0.3_225	H264 M-JPEG	1	1600x1200	1-way	2/1	-	-	Yes	
P606	2.0.3_225	H264 M-JPEG	1	1600x1200	1-way	-	-	-	Yes	
PB630	2.0.3_225	H264 M-JPEG	1	640x480	1-way	-	-	-	Yes	
PD634	2.0.3_225	H264 M-JPEG	1	640x480	1-way	-	-	-	Yes	
PD636	2.0.0_1	H.264	1	1600x1200	-	-	-	-	Yes	
Note:	Limited integration: camera supports video stream of H.264/1600x1200/15fps only, no other features									
PL621	2.0.3_225	H264 M-JPEG	1	1600x1200	1-way	1/1	-	-	Yes	
PV6901	2.0.3_225	H264 M-JPEG	1	720x480	1-way	1/1	Yes	-	Yes	
Note:	Focus function doesn't work properly in FW v2.5, which will be fixed in next version.									
Note:	All models: Image is broken easily when modifying camera parameter. All models: Remove motion detection function because camera FW is not ready for it. All models: Camera is easily disconnected as two M-JPEG stream existed, so dual stream function is disabled. However, the issue is remained if connecting same camera twice.									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Samsung										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNB-2000		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	Supported by design
SNB-3000		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design
SNC-B2315	2.01	MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	
SNC-B2331	v1.00_090810	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	
SNC-B2335	v1.10_100129	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	
SNC-B5368	v1.00_091001	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	
SNC-B5395	2.10	MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	
SNC-B5399	v1.10_091120	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	
SNC-C6225	1.01	MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	-	
SNC-C7225	1.01	MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	-	Supported by design
SNC-C7478	v1.01_090625	MPEG4 M-JPEG	1	720x576	1-way	8/4	Yes	Yes	-	
SNC-M300	v2.11_090729	MPEG4 M-JPEG	1	2048x1536	1-way	2/2	-	Yes	-	
SND-3080		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	Supported by design
SNV-3080		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

SANTEC										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNC-3901MDN	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Tested by manufacturer
SNC-390DN/W	1.5	MPEG4 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	Yes	
Note:	PTZ is only supported by external RS-485 device.									
SNC-5211MIR	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Tested by manufacturer
SNC-5211R/W	1.5	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	
SNC-5651R/W	1.5	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	
SNC-620/W	1.0.1.5	MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	Tested by manufacturer
SNC-6201M	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Tested by manufacturer
SNC-6701D/W	1.0.1.5	MPEG4 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	-	Tested by manufacturer
SNC-P3601M	3.1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Tested by manufacturer

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Sanyo										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
VCC-HD2100		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VCC-HD2100P		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VCC-HD2300		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VCC-HD2300P		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VCC-HD2500	CAM MAIN 1.00-10, CAM SUB 1.00-00, NET MAIN 1.00-06, NET SUB 1.00-01	H.264 M-JPEG	1	2288x1712	1-way	2/2	-	Yes	-	
VCC-HD2500P	CAM MAIN 1.00-10, CAM SUB 1.00-00, NET MAIN 1.01-02, NET SUB 0.00-00	H.264 M-JPEG	1	2288x1712	1-way	2/2	-	Yes	-	
VCC-HDN1 / VCC-HD4000 / VCC-HD4000P / VCC-HD4000PC	MAIN 1.05-04, SUB 1.00-03	H.264 M-JPEG	1	2288x1712	-	2/1	Yes	Yes	-	
Note:	PTZ support: zoom, preset, and focus									
VCC-HD4600	CAM MAIN 1.00-05, CAM SUB 1.00-01, NET MAIN 1.00-04, NET SUB 1.00-04	H.264 M-JPEG	1	2288x1712	1-way	2/2	Yes	Yes	-	
Note:	PTZ support: zoom, preset, and focus									
VCC-HD4600P		H.264 M-JPEG	1	2288x1712	1-way	2/2	Yes	Yes	-	Supported by design
VCC-HD5400		H.264 M-JPEG	1	2288x1712	1-way	4/2	Yes	Yes	-	Supported by design
VCC-HD5400P		H.264 M-JPEG	1	2288x1712	1-way	4/2	Yes	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

Sanyo										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
VCC-HD5600	CAM MAIN 1.00-04, CAM SUB 1.00-00, MEC MAIN 1.04-00, I/O MAIN 1.03-00, NET MAIN 1.00-04, NET SUB 1.00-02	H.264 M-JPEG	1	2288x1712	1-way	8/2	Yes	Yes	-	
Note:	PTZ Support: enable move feature is supported in NVRmini v2.3.2 and above version; 9~16 preset point are invalid in NVRmini v2.3.1 Max Resolution: 2288x1712(M-JPEG), 1920*1080(H.264)									
VCC-HD5600P		H.264 M-JPEG	1	2288x1712	1-way	8/2	Yes	Yes	-	Supported by design
Note:	PTZ Support: enable move feature is supported in NVRmini v2.3.2 and above version; 9~16 preset point are invalid in NVRmini v2.3.1 Max Resolution: 2288x1712(M-JPEG), 1920*1080(H.264)									
VDC-HD3100		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VDC-HD3100P		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VDC-HD3300	MAIN 1.00-14, SUB 1.00-02	H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	
VDC-HD3300P		H.264 M-JPEG	1	2288x1712	-	2/2	-	Yes	-	Supported by design
VDC-HD3500		H.264 M-JPEG	1	2288x1712	1-way	2/2	-	Yes	-	Supported by design
VDC-HD3500P		H.264 M-JPEG	1	2288x1712	1-way	2/2	-	Yes	-	Supported by design
Note:	Administrator privilege account / number: VCC-HD2100/2300/3100/3300: admin / 3; operator / 1 VCC-HD2500/3500/4600/5400/5600: admin / 1; operator / 2 VCC-HD4000: admin / 1									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307

Sony											
SONY											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
SNC-CH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	-	Yes	
SNC-CH160	1.13.00	H.264 MPEG4 M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Yes	
SNC-CH210	1.12.00	H.264 MPEG4 M-JPEG	1	2048x1536	-	-	-	Yes	-	Yes	
SNC-CH240	1.10.01	H.264 MPEG4 M-JPEG	1	1920x1440	1-way	1/2	-	Yes	-	Yes	
SNC-CM120	1.00	MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	-	Yes	
SNC-CS10		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Yes	Supported by design
SNC-CS11	1.05	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Yes	
SNC-CS20		MPEG4 M-JPEG	1	768x576	1-way	1/2	-	Yes	-	Yes	Supported by design
SNC-CS3		M-JPEG	1	736x480	-	1/2	-	-	-	Yes	Supported by design
SNC-CS50	2.21	MPEG4 M-JPEG	1	640x480	1-way	2/2	-	Yes	-	Yes	
SNC-DF40	1.17	MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	
SNC-DF50	1.11	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	
SNC-DF70	1.17	MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	
SNC-DF80	1.11	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	
SNC-DF85		H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	Supported by design
SNC-DH120	1.12.03	H.264 MPEG4 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	
SNC-DH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	-	Yes	
Note:	Motion detection will be turned off upon changing to maximum resolution. Remember to enable it in camera web.										
SNC-DH160	1.13.00	H.264 MPEG4 M-JPEG	1	1280x1024	-	1/1	-	Yes	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec



NUUO version 2.5.3_release date_110307

Sony											
SONY											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
SNC-DH180	1.10.02	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	-	Yes	
SNC-DH240	1.11.00	H.264 MPEG4 M-JPEG	1	1920x1440	1-way	1/2	-	Yes	-	Yes	
SNC-DM110		MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	-	Yes	Supported by design
SNC-DM160	1.01	MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	-	Yes	
SNC-DS10	1.01	H.264 MPEG4 M-JPEG	1	768x576	1-way	1/2	-	Yes	-	Yes	
SNC-DS60	1.00	MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	-	Yes	
SNC-P1	1.28	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Yes	
SNC-P5	1.11	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	-	Yes	
SNC-RH124	1.10.01	H.264 MPEG4 M-JPEG	1	1280x720	1-way	4/2	Yes	Yes	-	Yes	
SNC-RH164	1.10.01	H.264 MPEG4 M-JPEG	1	1280x720	1-way	4/2	Yes	Yes	-	Yes	
SNC-RS44N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS44P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS46N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS46P	1.10.02	H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	-	Yes	
SNC-RS84N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS84P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS86N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RS86P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	-	Yes	Supported by design
SNC-RX530	3.00	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	-	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

Sony											
SONY											
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
SNC-RX550		H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
SNC-RX570	3.01	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	-	Yes	
SNC-RZ25	1.29	MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	-	Yes	
SNC-RZ30	3.14	M-JPEG	1	736x480	-	3/2	Yes	-	-	Yes	
SNC-RZ50	2.21	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	-	Yes	
SNC-Z20	1.06	M-JPEG	1	736x480	-	1/2	Yes	-	-	Yes	
Note:	PTZ Support: zoom only.										
SNT-EP104		H.264 MPEG4 M-JPEG	4	720x480	-	-	-	Yes	-	Yes	Supported by design
SNT-EP154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	-	-	-	Yes	-	Yes	
SNT-EX101		H.264 MPEG4 M-JPEG	1	720x480	1-way	2/2	Yes	Yes	-	Yes	Supported by design
SNT-EX101E	1.10.01	H.264 MPEG4 M-JPEG	1	PAL: 720x576 NTSC: 720x480	1-way	2/2	Yes	Yes	-	Yes	
SNT-EX104	1.10.01	H.264 MPEG4 M-JPEG	4	PAL: 720x576 NTSC: 720x480	1-way	4/4	Yes	Yes	-	Yes	
SNT-EX154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	1-way	4/4	Yes	Yes	-	Yes	
SNT-V704	2.15	MPEG4 M-JPEG	4	720x480	1-way	1/4	-	-	-	Yes	


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

StarDot										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SD130B		M-JPEG	1	1296x960	-	-	-	Yes	-	Supported by design
SD130BN		M-JPEG	1	1296x960	-	-	-	Yes	-	Supported by design
SD130V	NetCamSC 1.1.63	M-JPEG	1	1296x960	-	-	-	Yes	-	
SD130VN		M-JPEG	1	1296x960	-	-	-	Yes	-	Supported by design
SD300B		M-JPEG	1	2048x1536	-	-	-	Yes	-	Supported by design
SD300V		M-JPEG	1	2048x1536	-	-	-	Yes	-	Supported by design
SD500B		M-JPEG	1	2595x1944	-	-	-	Yes	-	Supported by design
SD500BN	NetCamSC 1.1.63	M-JPEG	1	2595x1944	-	-	-	Yes	-	
SD500V		M-JPEG	1	2595x1944	-	-	-	Yes	-	Supported by design
SD500VN		M-JPEG	1	2595x1944	-	-	-	Yes	-	Supported by design
SDEXP2	ExpressXL 1.1.61	M-JPEG	2	704x480	-	-	-	Yes	-	
Note:	Camera doesn't support adjust framerate.									
SDEXP4	ExpressXL 1.1.63	M-JPEG	4	704x480	-	-	-	Yes	-	
Note:	Camera doesn't support adjust framerate.									
SDH130B		H264 M-JPEG	1	1296x976	-	1/0	-	Yes	-	Supported by design
SDH130V		H264 M-JPEG	1	1296x960	-	1/0	-	Yes	-	Supported by design
SDH130BN		H264 M-JPEG	1	1296x976	-	1/0	-	Yes	-	Supported by design
SDH130VN		H264 M-JPEG	1	1296x960	-	1/0	-	Yes	-	Supported by design
SDH300B		H264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	Supported by design
SDH300V		H264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

StarDot										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SDH500B		H264 M-JPEG	1	2560x1944	-	1/0	-	Yes	-	Supported by design
SDH500V		H264 M-JPEG	1	2560x1944	-	1/0	-	Yes	-	Supported by design
SDH500BN	1.1.68	H264 M-JPEG	1	2560x1944	-	1/0	-	Yes	-	
SDH500VN		H264 M-JPEG	1	2560x1944	-	1/0	-	Yes	-	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Toshiba										
TOSHIBA										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IKWB21A	2.09.E.200.121	M-JPEG	1	1280x960	1-way	-	Yes	-	-	
IKWB70A	0100e	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
IKWD01A	0100a	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

TRUEN										
TRUEN										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
TCAM-570	Enc:V1.103A-031	H.264 M-JPEG	1	1920x1080	1-way	2/2	Yes	Yes	-	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Videosec										
Videosec®										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IBF-211	5.0.2.3874	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	
IDA-210		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Tested by manufacturer
IP-206M	5.a.2.4031	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	
IS-240		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Tested by manufacturer
Note:	To solve the disconnection problems on SXGA resolution with quality 99 and 100, please upgrade to the following FW, which is certified by manufacturer. IBF-211 and IDA-210: 5.0.2.4437; IP-206M and IS-240: 5.a.2.4441									

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FD61x1		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	Supported by design
FD61x2		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	Supported by design
FD7130	0100e	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	
FD7131		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	Yes	Supported by design
FD7132	0100f	MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	Yes	
FD7141	0100g	MPEG4 M-JPEG	1	720x480	-	1/1	-	Yes	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
FD7160		MPEG4 M-JPEG	1	1600x1200	-	-	-	Yes	Yes	Supported by design
FD8133		H.264 MPEG4 M-JPEG	1	1280x800	-	1/0	-	Yes	Yes	Supported by design
FD8134	0100e	H.264 MPEG4 M-JPEG	1	1280x800	-	1/0	-	Yes	Yes	
FD8161	0100h	H.264 MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
FD8361	0100d1	H.264 MPEG5 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	
IP21x1		M-JPEG	1	720x576	-	1/1	-	Yes	Yes	Supported by design
IP21x2		M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP3132		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP3133		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP3135		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design
IP3135-PLNK		H.263	1	720x576	1-way	1/2	-	Yes	Yes	Supported by design
IP3136		H.263	1	720x576	1-way	-	-	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IP3136-PLNK		H.263	1	720x576	1-way	1/2	-	Yes	Yes	Supported by design
IP3137		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP31x1		H.263	1	720x576	-	1/1	-	Yes	Yes	Supported by design
IP31x1TLFN		H.263	1	720x576	-	1/1	-	Yes	Yes	Supported by design
IP31x2		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP31x7		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP51x2		MPEG4	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP51x4		MPEG4	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP6114		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP6124		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP61x2		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP61x4		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP61x7		MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7130	0100c	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
IP7131		MPEG4	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7132		MPEG4	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7133	0100b	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
IP7134	0100b	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
IP7135		MPEG4	1	704x576	1-way	-	-	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IP7137		MPEG4	1	704x576	1-way	-	-	Yes	Yes	Supported by design
IP7138	0101h	MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	
IP7139		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
IP7142		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7151		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7152		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7153		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
IP7154	0100b	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	
IP7160	0101b	MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	
IP7161		MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
IP71x7		MPEG4	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
IP7251	0100f	MPEG4	1	640x480	1-way	1/1	Yes	Yes	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
IP7330		MPEG4 M-JPEG	1	640x480	-	1/0	-	Yes	Yes	Supported by design
IP7361		MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
IP8151	0200a	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	*
Note:	This camera FW is under testing by manufacturer, so there are two issues existed which should be fixed in the official release: video stream of M-JPEG is not continuous; there is an image problem on resolution 176x144 @H.264.									
IP8161	0100k	H.264 MPEG4 M-JPEG	1	1600x1200	1-way	1/1	Yes	Yes	Yes	
IP8330	0100e	H.264 MPEG4 M-JPEG	1	640x480	-	1/0	-	Yes	Yes	

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec


NUUO version 2.5.3_release date_110307

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IP8332		H.264 MPEG4 M-JPEG	1	1280x800	-	1/0	-	Yes	Yes	Supported by design
IZ7151		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: zoom only.									
PT3134		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PT31x2		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PT31x3		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PT31x4		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PT31x7		H.263	1	720x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PT7000		MPEG4	1	720x576	1-way	-	Yes	Yes	Yes	Supported by design
PT7135		MPEG4	1	720x576	1-way	-	Yes	Yes	Yes	Supported by design
PT7137		MPEG4	1	704x576	1-way	-	Yes	Yes	Yes	Supported by design
PZ61x2		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PZ61x4		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PZ7131	0100b	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	
PZ7151	0101b	MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
PZ7152		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PZ71X1		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
PZ71X2		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	Supported by design
SD61x2		MPEG4 M-JPEG	1	720x576	1-way	4/1	Yes	Yes	Yes	Supported by design


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

VIVOTEK										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SD7151	0101d	MPEG4 M-JPEG	1	720x576	1-way	4/1	Yes	Yes	Yes	
Note:	No audio support in M-JPEG format. MPEG4: Unable to connect through HTTP.									
SD73X3		MPEG4 M-JPEG	1	704x576	1-way	4/1	Yes	Yes	Yes	Supported by design
TC5330		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Supported by design
TC5331		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
TC5630		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
TC5631		MPEG4	1	720x576	1-way	-	-	Yes	Yes	Supported by design
VS2101		M-JPEG	1	720x576	-	1/1	-	Yes	Yes	Supported by design
VS2401		M-JPEG	4	720x576	-	4/2	-	Yes	Yes	Supported by design
VS2402		M-JPEG	4	720x576	-	4/2	-	Yes	Yes	Supported by design
VS2403	0103b	M-JPEG	4	720x576	1-way	4/4	Yes	Yes	Yes	
VS3100		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
VS3101		H.263	1	720x576	-	1/1	-	Yes	Yes	Supported by design
VS3102		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
VS3102- XLTH		H.263	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
VS7100	0101e	MPEG4 M-JPEG	1	720x576	-	1/1	Yes	Yes	Yes	
Note:	MPEG4: Unable to connect through HTTP.									
VS8102		H.264 MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	Supported by design
Note:	Audio: All cameras don't support AAC audio codec, but GSM-AMR.									


Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

Zavio										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
B5110	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
B6110	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
D510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
D520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
D610A	LM.1.6.16	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	
D6111	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
D611E	LM.1.6.16	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	
F210A	LM.1.6.15	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	
F3100	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Supported by design
F3105	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Supported by design
F312A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
F5100	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
F5105	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
F510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F5110	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
F5115	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
F511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO

NVRmini Supported Camera Spec

NUUO version 2.5.3_release date_110307

Zavio										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
F520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F521E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F610A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
F611E	LM.1.6.16.00 7	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	
F721A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Supported by design
F731E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Supported by design
M510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: pan and tilt only									
M510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: pan and tilt only									
M511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: pan and tilt only									
M511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: pan and tilt only									
P5110	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Supported by design
Note:	PTZ Support: pan and tilt only									
P5115	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	
Note:	PTZ Support: pan and tilt only									
V111T	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Supported by design

Supported by design: This camera shares the same API with tested cameras, but has not been tested or validated by NUUO